

NOTE: SOME SYMBOLS SHOWN ON THIS LEGEND MAY NOT PERTAIN TO THIS PROJECT.





TLC SOLUTIONS 13099 S. Cleveland Avenue, Suite 500 Fort Myers, FL 33907 P 239.275.4240 www.tlc-engineers.com TLC No.:721030 THINK, LISTEN, CREATE.

REVISIONS

Description Date

Ω

(1)

王

REVISIONS No. Description Date

This item has been digitally signed and sealed by, Brett L.Sands, PE on the date adjacent to the seal. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies.

TLC ENGINEERING SOLUTIONS 13099 S. Cleveland Avenue, Suite 500 Fort Myers, FL 33907 P 239.275.4240 ort Myers, FL 33907 COA 15
239.275.4240 www.tlc-engineers.com
TLC No.:721030
THINK, LISTEN. CREATE.

Luminaire Schedule 0.900 LT-22-L27-840-AF-DIM-UNV SIGNIFY GARDCO ECF-S-32L-1A-NW-G2-4-HIS 1.000 ECF-S-32L-1A-NW-G2-5 SIGNIFY GARDCO 1.000 ECF-S-32L-700-NW-G2-4-HIS 2.000 PMC0-4-SF-UNV-4K-CRI83-38L_ 3,762 LUMENS 1.000 2@180_ECF-S-32L-530-NW-G2-4 1.000 Lance 6 Series _ 100W(Down_50W METEOR Lighting Up_50W) _ 4000K(CRI85)_ Down_ 60deg Up_60deg _ Fo


TARGETING: LEE COUNTY N.A. readings taken at grade
10.92 readings taken at grade
2.12 readings taken at grade PARKING: - 0.8 FC MIN CANOPY A - 4:1 AVG/MIN CANOPY B readings taken at grade BOUNDARY: - 0.5 FC MAX CANOPY: - 6.0 FC MIN LOUNGE_Workplane - 5:1 AVG/MIN PARKING

- LUMINAIRE TYPE F IS MOUNTED AT 10' AFF FROM GRADE TO THE CENTER OF THE LUMINAIRE - LUMINAIRES PLACED AT PROPOSED & SPECIFIED LOCATIONS


- LUMINAIRES NOT SPECIFIED WERE NOT CONSIDERED FOR CALCULATIONS - LUMINAIRE SYMBOLS ARE MAGNIFIED FOR LEGIBILITY







SITE PLAN - LIGHTING 1 PHOTOMETRICS 1" = 30'-0"



1 SITE PLAN - ELECTRICAL 1" = 20'-0"

PROVIDE (3) 3/4" CONDUITS WITH PULL STRING

MOUNT IN NEMA 4X

ENCLOSURE. COORDINATE ALL WORK WITH TECHNOLOGY

AND TERMINATED IN AN IN-GROUND BOX TO

BE USED FOR GATE CONTROLS. TYPICAL

ELECTRICAL KEY NOTES

YNOTE TEXT


- ROUTE 3 4" CONDUITS WITH PULL STRING FROM INGROUND JUNCTION BOX STUBBED UP IN ELECTRICAL ROOM FOR FUTURE 480V SERVICE.
- ROUTE 1 4" CONDUIT WITH PULL STRING FROM ELECTRICAL ROOM TO INGROUND BOX FOR FUTURE EV BUS CHARGING STATION. COORDINATE LOCATION.
- CHARGING STATION. COORDINATE LOCATION.

 PROVIDE A 208V TO 240V BUCK BOOST TRANSFORMER TO SUPPLY THE GRINDER STATION 30A, 240V, NEMA 3R
 DISCONNECT. PROVIDE THE DISCONNECT, TRANSFORMER AND ALL INTERCONNECTING WIRING AS RECOMMENDED
 BY THE GRINDER STATION MANUFACTURER.

LIGHTNING PROTECTION GENERAL NOTES

- THE COMPLETED INSTALLATION WILL MEET THE INSTALLATION REQUIREMENTS FOR "LIGHTNING PROTECTION SYSTEMS, (UNDERWRITERS LABORATORIES) UL96A" 12TH EDITION, AND SHALL COMPLY WITH NFPA 780. THE UL LIGHTNING PROTECTION INSPECTION CERTIFICATE WILL BE FURNISHED TO THE CONTRACTING OFFICER UPON COMPLETION OF THE SYSTEM.
- ALUMINUM COMPONENTS OF THE LIGHTNING PROTECTION SYSTEM WILL NOT BE MOUNTED ON OR TO COPPER SURFACES. COPPER COMPONENTS WILL BE USED TO AVOID ELECTROLYTIC CORROSION.
- METAL BODIES WITHIN 6'-0" OF THE LIGHTNING PROTECTIONS SYSTEM WILL BE BONDED TO THE SYSTEM IN ACCORDANCE WITH THE REQUIREMENTS OF THE UL96A 12TH EDITION.
- UNDERGROUND METALLIC PIPING ENTERING THE BUILDING WILL BE BONDED TO THE LIGHTNING PROTECTION GROUNDING SYSTEM
- ADHESIVE USED WITH AIR TERMINAL BASES AND CONDUCTOR FASTENERS WILL BE "M1 STRUCTURAL SEALANT" TYPE VERIFIED WITH THE CONTRACTING OFFICER. TERMINALS MOUNTED ON THE STANDING SEAM METALLIC ROOF SHALL BE CLAMPED ONTO THE SEAM. AT NO POINT SHALL THE METALLIC ROOF BE PENETRATED.
- ROOFTOP EQUIPMENT WILL BE PROTECTED AS REQUIRED INCLUDING THE INSTALLATION OF AIR TERMINALS AND OR BONDING. IF THE METAL THICKNESS OF AN OBJECT IS 3/16" OR GREATER, AIR TERMINAL MAY BE ELIMINATED.

- 7. AIR TERMINALS WILL BE LOCATED AS SHOWN. THEY ARE TO BE A MAXIMUM OF 24" FROM THE ROOF EDGE AND PROJECT A MINIMUM OF 10" ABOVE THE PROTECTED EDGE. AIR TERMINALS THAT EXTEND 24" ABOVE THE PROTECTED EDGE WILL NOT EXCEED A SPACING GREATER THAN 25'.
- 8. ALL LIGHTNING PROTECTION SYSTEM CONDUCTORS WILL MAINTAIN A HORIZONTAL OR DOWNWARD PATH. ALL BENDS IN THE CONDUCTOR WILL HAVE A RADIUS BEND OF 8 INCHES OR GREATER, AND WILL HAVE AN ANGLE BEND OF 90 DEGREES OR GREATER.
- 9. ALL COMPONENTS OF LIGHTNING PROTECTION SYSTEM ARE NOT SHOWN, HOWEVER, A COMPLETE SYSTEM WILL BE PROVIDED TO INCLUDE ALL ROOF-TOP MOUNTED EQUIPMENT AND MEET "MASTER LABEL" REQUIREMENTS.
- ROOF PADS, PAVERS, FLASHINGS OR ANY OTHER SPECIAL ROOFING MATERIALS REQUIRED FOR INSTALLATION OF THE LIGHTNING PROTECTION SYSTEM WILL BE PROVIDED.
- ALL DOWN CONDUCTORS, THRU ROOF, WILL BE PROVIDED WITH A WATER TIGHT INSTALLATION TO PREVENT ROOF LEAKS. ALL DOWN CONDUCTORS SHALL BE PROTECTED A MINIMUM OF 6 FEET ABOVE GRADE.



TLC ENGINEERING
S O L U T I O N S

13099 S. Cleveland Avenue,
Suite 500
Fort Myers, FL 33907
P 239.275.4240
Www.tlc-engineers.com
TLC No.:721030
THINK. LISTEN. CREATE.

No. Description Date


ACRES PARK AND RIDE


LEHIGH

This item has been digitally signed and sealed by, Brett L.Sands, PE on the date adjacent to the seal. Printed copies of this document are not considered signed and sealed and the signature must be verified on any electronic copies. TLC SOLUTIONS

13099 S. Cleveland Avenue,
Suite 500
Fort Myers, FL 33907
P 239.275.4240

COA 15
www.tlc-engineers.com
TLC No.:721030 uite 500
ort Myers, FL 33907
239.275.4240
THINK, LISTEN. CREATE. E102





ENLARGED SITE PLAN -

2 ELECTRICAL LIGHTING
1/8" = 1'-0"


ELECTRICAL KEY NOTES


2 INDOOR UNIT RECEIVES POWER FROM THE OUTDOOR UNIT. PROVIDE ALL INTERCONNECTING WIRING.

1 FUTURE 480V DISTRIBUTION PANEL FOR BUS EV CHARGING.


KEYNOTE TEXT

EXHAUST FAN TO BE CONTROLLED WITH LIGHT FIXTURES THROUGH OCCUPANCY SENSOR. CONNECT TO THE 120V LIGHTING CIRCUIT SERVING THE ROOM.






This item has been digitally signed and sealed by, Brett L.Sands, PE on the date adjacent to the seal. Printed copies



FLOOR PLAN - ELECTRICAL 1 LIGHTING 1/4" = 1'-0"




REVISIONS

No. Description Date

	ELECTRICAL MECHANICAL EQUIPMENT SCHEDULE													
	FLA CIRCUIT DISCONNECT													
TAG	HP	(AMPS)	LOAD	VOLTAGE	PHASE	PANEL	NUMBER	BREAKER	Conduit and Wire Size	SWITCH SIZE	NO. OF POLES	ENCLOS. TYPE	FURN. BY (DIV.)	COMMENTS
AHU-1			1080 VA	208 V	3	LP1	10,12,14	15	(3) #10, (1) #10 GND, 3/4" RACEWAY	30A	3	NEMA 1	26	AHU-1
CU-1			7200 VA	208 V	3	LP1	9,11,13	40	(3) #8, (1) #10 GND, 3/4" RACEWAY	60A	3	NEMA 3R	26	CU-1
CU-2			1456 VA	208 V	1	LP1	15,17	15	(3) #10, (1) #10 GND, 3/4" RACEWAY	30A	2	NEMA 3R	26	CU-2
CU-3			1456 VA	208 V	1	LP1	16,18	15	(3) #10, (1) #10 GND, 3/4" RACEWAY	30A	2	NEMA 3R	26	CU-3
EWH-1			4500 VA	208 V	3	LP1	22,24,26	20	(3) #10, (1) #10 GND, 3/4" RACEWAY	30A	3	NEMA 1	26	EWH-1

	LIG	HTING FIXTURE SO	HEDU	LE	
TYPE	DESCRIPTION	MANUFACTURER / MODEL	LAMP SOURCE	FIXTURE WATTAGE W/LF	COMMENTS
А	2' X 2' LED RECESSED FIXTURE, 2700 LUMENS, 4000K, ACRYLIC FROSTED LENS, DIMMABLE	WILLIAMS: LT-2-2-L27-840-AF-DIM-UNV	LED	21.30 W	
B4	SITE LIGHTING LED POLE MOUNTED FIXTURE, 14,000 LUMEN, 4000K, TYPE 4 DISTRIBUTION	SIGNIGY GARDCO: ECF-S-32L-1A-NW-G2-AR-4-UNV-FINISH/PTF2-EC F-S/L-1-90		159.00 W	
В4-Н	SITE LIGHTING LED POLE MOUNTED FIXTURE, 14,000 LUMEN, 4000K, TYPE 4 DISTRIBUTION, WITH HOUSE SIDE SHIELD	SIGNIGY GARDCO: ECF-S-32L-1A-NW-G2-AR-4-HIS-FINISH/PTF2-EC F-S/L-1-90		159.00 W	
B5-2	SITE LIGHTING LED POLE MOUNTED BACK TO BACK FIXTURES, 14,000 LUMEN EACH, 4000K, TYPE 5 DISTRIBUTION	SIGNIFY/GARDCO: 2 @ 180-ECF-S-32L-1A-NW-G2-5-UNV-FINISH/PTF2-E CF-S/L-2-180		318.00 W	
C4-H	SITE LIGHTING LED POLE MOUNTED FIXTURE, 14,000 LUMEN, 4000K, TYPE 4 DISTRIBUTION, WITH HOUSE SIDE SHIELD	SIGNIGY GARDCO: ECF-S-32L-700-NW-G2-AR-4-UNV-HIS-FINISH/PT F2-ECF-S/L-1-90		110.00 W	
D	LED LINEAR STRIP, 4', ROUND FROSTED LENS, 5000 LUMENS, 4000K, DIMMABLE	WILLIAMS: 75R-4-L50-840-DIM-UNV	LED	33.00 W	
D4-2	SITE LIGHTING LED POLE MOUNTED BACK TO BACK FIXTURES, 10,000 LUMEN EACH, 4000K, TYPE 4 DISTRIBUTION	SIGNIFY/GARDCO: 2 @ 180-ECF-S-32L-530-NW-G2-4-UNV-FINISH/PTF2-E CF-S/L-2-180		318.00 W	
EM	EMERGENCY LED FIXTURE WITH WET LOCATION HOUSING WHERE INDICATED	BEGHELLI: PEH-1 (WL)			
EX	LED EXIT LIGHT FIXTURE WITH RED LETTERING, EMERGENCY BATTERY BACK-UP AND INTEGRAL LED TEST SWITH. ALUMINUM HOUSING, UNIVERSAL MOUNT	BEGHELLI: LC1-E-SA-LR-U-AL-W	LED	3.00 W	
F	6" UP/DOWN CYLINDER, EXTRUDED ALUMINUM CONSTRUCTION, 10,018 LUMENS, 60 DEGREE UPPER OPTIC, FORWARD THROW LOWER OPTIC, 80 CRI, WET LOCATION LISTED, DIMMABLE, 4000K	METEOR: LA6-100-408-UNV-STVS-60-FINISH-OUT	LED	100.00 W	
G	1' X 4' SURFACE MOUNT LED, VAPOR TIGHT, VANDAL RESISTANT, 6200 LUMENS, 4000K, CLEAR, UV STABILIZED POLYCARBONATE, .15" SHIELDING	WILLIAMS: AVX-4-L62-840-CPC-DIM-UNV	LED	57.00 W	
Н	2" x 4' NARROW LED INDUSTRIAL GRADE SURFACE MOUNT STRIP FIXTURE. VAPORTIGHT, LISTED FOR WET LOCATION.4000K	PARAMOUNT: PMCO-4-SF-UNV-4K-CRI83-38L-PZ-L4-LD	LED	32.00 W 8.00 W	




1 ELECTRICAL RISER DIAGRAM N.T.S.

COPPER CONDUCTOR/FEEDER SCHEDULE (90/75 RATED)												
SYMBOL	NUMBER OF SETS	PHASE CONDUCTORS (QUANTITY) SIZE - AWG	NEUTRAL CONDUCTORS (QUANTITY) SIZE - AWG	GROUNDING CONDUCTORS (QUANTITY) SIZE - AWG	CONDUIT SIZE (QUANTITY) SIZE	REMARKS						
400	2	(3) #3/0	(1) #3/0	(1) #3	(1) 2" FOR EACH RUN							
SVC400	2	(3) #3/0	(1) #3/0		(1) 2" FOR FACH RUN							


Supply From: LP1 Enclosure: TYPE 1 Ma						Dist. / Phase / Wires: 120/208 Wye / 3 / 4 K.A.I.C. Rating: Max Height Busing: Yes Mains Type: M						BUS Rating: 100 A				
	CKT		Trip(A)	Р		(VA)						Trip(A		СКТ		
	1	RECEPTACLE - IT RACK	20	1		1.000					1	20	RECEPTACLE - ACCESS CONTROL	2		
		RECEPTACLE - SERVICE PROVIDER EQUIPMENT	20	1			0.800	1.360			1	20	RECEPTACLES - I.T. 7	4		
		KIOSK	20	1					0.500	0.550	1	20	DIGITAL DISPLAY - CANOPY	6		
	7	BUS SCHEDULE - CANOPY	20	1	0.550	0.550					1	20	DIGITAL DISPLAY - CANOPY	8		
		DIGITAL DISPLAY - CANOPY	20	1			0.550	0.550			1	20	BUS SCHEDULE - CANOPY	10		
		DIGITAL DISPLAY - CANOPY	20	1					0.550	0.200	1	20	RECEPTACLE - SITE CAMERA POWER	12		
	13	RECEPTACLE - SITE CAMERA POWER	20	1	0.400	0.400					1	20	RECEPTACLE - SITE CAMERA POWER	14		
		RECEPTACLE - SITE CAMERA POWER	20	1			0.200	0.000			1	20	Spare	16		
		RECEPTACLE - SITE CAMERA POWER	20	1					0.200	0.000	1	20	Spare	18		
		Spare	20	1	0.000	0.000					1	20	Spare	20		
		Spare	20	1			0.000	0.000			1	20	Spare	22		
		Spare	20	1					0.000	0.000	1	20	Spare	24		
		Spare	20	1	0.000	0.000					1	20	Spare	26		
		Spare	20	1			0.000	0.000			1	20	Spare	28		
		Spare	20	1				1	0.000		1		Space	30		
		Spare	20	1	0.000						1		Space	32		
		Spare	20	1			0.000				1		Space	34		
		Space		1							1		Space	36		
		Space		1		0.000							- Part	38		
		Space		1		0.000		0.000			3	30	SPD	40		
		Space		1				0.000		0.000				42		
		Connected Phas	e Load (K	VA)	4.	100	3.	460	2.0	000				1 1		
		Connected Ph	`	,		.038		.705		667	J					
.oa	d CI	assification			cted Loa	d C	emand F	actor	Demand Load				Panel Totals			
QUII	PMEN	Т		330	00 VA		100.00%		3300 VA							
ECE	PTAC	LE		62	60 VA		100.00%	6	62	60 VA		Total	Connected Load (KVA): 9.560			
													tal Demand Load (KVA): 9.560			
													otal Demand Current (A): 27			
													tai Boillana Garront (71). 21			
												-				
						-						-				
)and	l Ko	unotes (KN):														
ane	l Key	ynotes (KN):														


		ting: SURFACI sure: TYPE 1	E		Dist. / Phase / Wires: 120/208 Wye / 3 / 4 K.A.I.C. Rating: BUS Rating: 400 A Max Height Busing: Yes Mains Type: MCB MCB Rating: 400										
N CKT		Trip(A)	Р		Α	В					Trip(A)	Circuit Description	скт ки		
1	RECEPTACLE - VENDING	20	1	0.600	0.600					1	20	RECEPTACLE - VENDING	2		
3	RECEPTACLE - VENDING	20	1			0.600	1.300			1	20	TOILET 1 - HAND DRYER	4		
5	MENS 5 - HAND DRYER	20	1					1.300	1.300	1	20	MENS 5 - HAND DRYER	6		
7	WOMEN 6 - HAND DRYER	20	1	1.300	1.300					1	20	WOMEN 6 - HAND DRYER	8		
9						2.400	0.360						10		
2 11	CU-1	40	3					2.400	0.360	3	15	AHU-1	12		
13				2.400	0.360								14		
15	- CU-2	15	2			0.728	0.728			2	15	CU-3	16		
17								0.728	0.728	Ш			18		
	Spare	20	1	0.000	0.000					1	20	Spare	20		
	EF-2	20	1			0.300	1.500	0.700	4 =00		00	5.44.4	22		
	RECEPTACIES - RMS 1,2	20	1	0.540	4.500			0.720	1.500	3	20	EWH-1	24		
	RECEPTACIES - LOUNGE 2	20	1	0.540	1.500	0.540	0.000			4	00	DECEDIACIES DAGES	26		
	RECEPTACLES - RMS 3,4	20	1			0.540	0.360	0.500	0.700	1	20	RECEPTACIES - RMS 5,6	28		
	RECEPTACLE - EWC	20	1	0.400	0.700			0.500	0.720	1	20	RECEPTACLES - EXTERIOR	30		
	LEE TRAN SIGN	20	1	0.180	0.720	4.050	1.000			1	20	RECEPTACLES - CANOPY TABLE	32		
	LIGHTING - BUILDING RECEPTACLES - CANOPY TABLE	20	1			1.259	1.200	0.900	1 000	1	20 20	RECEPTACLE - LOUNGE 2 - MICRO RECEPTACLE - LOUNGE 2 - REF	34		
			1	1 200	1 000			0.900	1.200	1			36		
	FIRE ALARM PANEL	20	1	1.200	1.800	1 100	0.400			1	20 20	LIGHTING - CANOPY	38		
41	LIGHTING - CANOPY GATE OPERATOR	20	1			1.400	0.160	0.720	0.720	1	20	LIGHTING - SMALL CANOPY GATE OPERATOR	40		
43	GATE OPERATOR	20		4.100	0.720			0.720	0.720	1	20	GATE OPERATOR GATE OPERATOR	42		
	PANEL UPS	100	3	4.100	0.720	3.460	0.200			1	20	MONUMENT SIGN LIGHT	46		
47	PAINEL UPS	100	٦			3.400	0.200	2.000	1.407	- 1	20	MONOMENT SIGN LIGHT	48		
49				2.500	1.407			2.000	1.407	2	20	SITE LIGHTING	50		
1 51	GRINDER STATION	30	2	2.300	1.407	2.500	0.000			1	20	Spare	52		
	Spare	20	1			2.300	0.000	0.000	0.000	1	20	Spare	54		
55	Spare	20	1	0.000	0.000			0.000	0.000	1	20	Spare	56		
57	Spare	20	1	0.000	0.000	0.000	0.000			1	20	Spare	58		
	Spare	20	1					0.000	0.000	1	20	Spare	60		
	Spare	20	1	0.000	0.000					1	20	Spare	62		
	Spare	20	1			0.000	0.000			1	20	Spare	64		
	Spare	20	1					0.000	0.000	1	20	Spare	66		
	Spare	20	1	0.000						1		Space	68		
69	Spare	20	1			0.000				1		Space	70		
71	Space		1							1		Space	72		
73	Space		1							1		Space	74		
75	Space		1							1		Space	76		
77	Space		1							1		Space	78		
	Space		1		0.000					ĮĪ			80		
	Space		1				0.000			3	30	SPD	82		
83	Space		1						0.000				84		
		Phase Load (KV	-		122		.965	1	003						
		ed Phase Amps		178).557		.695			. .=			
	lassification	Conr		ted Loa	d D	emand F			nd Load	l		Panel Totals			
QUIPMEN	IT			75 VA		100.00%			675 VA			0 (11 1/0/4)			
GHTING				03 VA		100.00%			603 VA			Connected Load (KVA): 57.083			
otor				0 VA		125.00%			75 VA			tal Demand Load (KVA): 56.139			
ther	N.=			00 VA		100.00%			200 VA		To	tal Demand Current (A): 156			
	ECEPTACLE			40 VA		81.97%			820 VA						
VAC			156	92 VA		111.47%	b	174	492 VA						

1. ROUTE 2#10 & 1#10 GND IN 3/4" CONDUIT. 2. ROUTE 3#8 & 1#10 GND IN 3/4" CONDUIT.












EQUIPMENT NAMEPLATE

2 DETAIL N.T.S.







5 SPD INSTALLATION DETAIL N.T.S.

PANEL "XXXX"

FED FROM PANEL "XXXX"

VIA T-XXX

TYPICAL 120/208V PANELBOARD

PANEL "XXX"

TYPICAL 277/480V PANELBOARD

~ 277/480V, 3ø, 4W → FED FROM PANEL "XXXX"


1/16" THICK WHITE PLASTIC WITH COLORED FACE PER

PANELBOARD VOLTAGE

PANELBOARD SOURCE

3 PANELBOARD NAMEPLATE N.T.S.

SPECIFCIATIONS



This item has been digitally signed and sealed by, Brett L.Sands,

PE on the date adjacent to the seal. Printed copies of this document are not

considered signed and sealed and the signature must be verified on any electronic copies.

TLC ENGINEERING

THINK, LISTEN, CREATE,

www.tlc-engineers.com TLC No.:721030

13099 S. Cleveland Avenue,

Fort Myers, FL 33907

P 239.275.4240

Suite 500